

HISTORIC DISTRICT REVIEW EXHIBIT LIST

Applicant: COSM

Property Address: Fremont St

Hearing Date: November 4, 2021, **December 2, 2021**

Application Number: HD-21-765

1. Application HD-21-765 to St. Michaels Historic District Commission.
2. Certificate of Appropriateness HD-12-332 Addendum 1
3. Aerial photo
4. Proposed location photo
5. Existing comfort station photos

Entered into the record on the December 2, 2021 meeting:

6. Certificate of Appropriateness HD-21-765
7. Photos – existing comfort station
8. Detail sheet American Building Components



THE COMMISSIONERS OF ST. MICHAELS

OFFICE OF CODE ENFORCEMENT, PLANNING AND ZONING

300 MILL STREET

P.O. BOX 206

ST. MICHAELS, MD 21663

SETTLED 1670-1680


INCORPORATED 1804

TELEPHONE: 410.745.9535

FACSIMILE: 410.745.3463


TO: Historic District Commission
FROM: Kymberly Kudla, Zoning Officer
DATE: 11/04/2021
RE: HD-21-765
Address: Fremont Street Parking Lot
Applicant: COSM

The applicant is proposing to construct a comfort station (restroom). No setback or lot coverage issues. No other zoning issues noted at this time.



NORTH WEST VIEW EXISTING LOCATION 










⑦



SOUTH WEST VIEW EXISTING LOCATION

⑤



Panel	Applications	Coverage	Rib	Panel Attachment	Gauges	Finishes	Coatings	UL
 <p>1 1/4 Corrugated</p>	Roof and Wall	24"	1 1/4" Spacing 1/4" Height	Exposed Fastening System	32, 29, 26	Bare	Galvalume Plus®, G-40 Galvanized	Class A UL Fire Rating
 <p>2 1/2 Corrugated</p>	Roof and Wall	24"	2 1/2" Spacing 1/2" Height	Exposed Fastening System	29, 26	Bare	Galvanized, Galvalume Plus®	N/A
 <p>5V Crimp</p>	Roof	24"	12" Spacing 1/2" Height	Exposed Fastening System	32, 29, 26	Bare and Siliconized Polyester	Galvalume Plus®, Signature® 200, G-40 Galvanized	UL 580 rating, UL 263 for internal fire, UL 2218 Class 4 impact rating, UL 790 - Class A Fire Rating
 <p>7/8 Wide Rib®</p>	Roof and Wall	36"	12" Spacing 7/8" Height	Exposed Fastening System	29, 26	Bare and Siliconized Polyester	Galvanized, Galvalume Plus®, Signature® 200	Class A UL Fire Rating, Class 4 UL Impact Rating
 <p>Ameri-Drain®</p>	Roof and Wall	36"	6" Spacing 1/2" Height	Exposed Fastening System	29, 26	Bare and Siliconized Polyester	Galvanized, Galvalume Plus®, Signature® 200	Class A UL Fire Rating, Class 4 UL Impact Rating
 <p>Imperial Rib®</p>	Roof and Wall	36"	9" Spacing 3/4" Height	Exposed Fastening System	29, 26	Bare and Siliconized Polyester	Galvanized, Galvalume Plus®, Signature® 200	UL 580 rating, UL 790, Class A for external fire, UL 263 for internal fire, UL 2218 Class 4 impact rating, Imperial Rib® carries Florida approval.
 <p>LokSeam</p>	Roof	12", 16", 18"	1 3/4" Height	Concealed Fastening System	24 (Standard), 22, 26 (Optional - 12" only)	Bare, Siliconized Polyester, Kynar and Metallic	Galvalume Plus®, Signature® 200, Signature® 300, Signature® 300 Metallic	UL Fire Resistance ratings, UL 90 Wind Uplift ratings, ASTM E1592 Structural Performance Uplift Certification
 <p>Monarch Rib®</p>	Roof and Wall	36"	9" Spacing 5/8" Height	Exposed Fastening System	29, 26	Bare and Siliconized Polyester	Galvanized, Galvalume Plus®, Signature® 200	Class A UL Fire Rating, Class 4 Impact UL 2218
 <p>PBC</p>	Roof and Wall	32"	2.67" Spacing 7/8" Height	Exposed Fastening System	26 (Standard); 29, 24, 22 (Optional)	Bare, Siliconized Polyester and Kynar	Galvalume Plus®, Signature® 200, Signature® 300	UL 790 external fire rating